

Sound Level Meter

**2310 SL**

FEATURES

- Max. & Min. function
- Over & under range indication
- 4-digit LCD with bar graph
- Frequency weighting characteristic for 2 times per second
- AC signal output
- Low battery indication

SPECIFICATIONS

Measuring ranges	Lo: 30dB~80dB Med: 50dB~100dB Hi: 80dB~130dB
Accuracy	±1.5dB (at Reference Range)
Reference sound level & frequency	94dB, 1kHz
Resolution	0.1dB
Detector-indicator characteristic	Fast: 125ms Slow: 1s
Analogue signal output	AC 1Vrms for each range
Dimensions	240(L) x 62(W) x 39(D)mm
Weight (battery included)	Approx. 224g
Power source	9V (6F22) × 1
Safety standard	IEC 651 Type 2 & ANSI S1.4 Type 2 EN 61326-1
Accessories	Instruction manual Adjusting bar Sponge cover Carry case Battery

Light Meter

**2330 LX**

FEATURES

- Wide range of measurements, up to 40000 lux and 4000 fc
- 0.01 lux and 0.001 fc resolution for accurate low-light measurements
- Light sensor cover is included for preserving sensor life
- Auto off function
- Data hold function
- Low battery indication
- Over range indication
- Auto or manual ranging
- Calibration mode is provided
- 9V battery system
- Selection key for lux or fc
- Spectral sensitivity close to CIE photopic curve
- Ideal tool for workplace, clean-room and computer room light testing
- Video, photographic, office, classroom, and architectural uses

SPECIFICATIONS

Measuring ranges	39.99 / 399.9 / 3999 / 39990 lux 3.999 / 39.99 / 399.9 / 3999fc
Resolution	0.01 lux - 10 lux 0.001 fc - 1 fc
Accuracy	±(3%rdg+5dgt) Calibrated to standard incandescent lamp, 2856°K.
Display	4000 count LCD
Photo sensor	Silicon photodiode
Operating / storage conditions	0°C ~ 40°C < 80 % R.H. -10°C ~ 50°C < 80 % R.H.
Dimensions	194(L) x 62(W) x 34(D)mm
Weight (battery included)	Approx. 245g
Power source	9V (6F22) × 1
Safety standard	EN 61326-1
Accessories	Instruction manual Carry case Battery