



AR63A Vibration Meter

Type: AR63A

Product introduction

Vibration meter(also called vibration severity) uses Piezoelectric Acceleration Transducer transfer

Category

(AR)Vibration Meter



FEATURES

Vibration meter(also called vibration severity) uses Piezoelectric Acceleration Transducer transfer the vibration signal in to electrical signal, analyze the input signals, and show the Acceleration, speed, shift of the vibration. It is widely used in the lines of Power, petrochemical, machinery manufacturing, metallurgy, vehicles, etc.

SPECIFICATIONS

Measuring Principle	Piezoelectric Ceramic Accelerometer (shear-type)
Acceleration Range	0.1~199.9m/s ²
Velocity Range	0.1~199.9m/s
Displacement Range	0.001~1.999mm
Acceleration Frequency Range	10Hz~1KHz (LO) 1KHz~15KHz (HI)
Velocity Frequency Range	10Hz~1KHz

Displacement Frequency Range	10Hz~1KHz
Accuracy	±5%H ±2 digits
Signal Output	AC output 2V peak (Display full scale)
Max Hold Function	---
Temperature Measurement	---
°C/°F Selection	---

PACKING INFORMATION

Power	9V Battery
Product Net Weight	147g
Product Size	183*67*30mm
Packing Style	Aluminum Box
Standard Quantity Per Carton	12PCS
Standard Carton Size	45*32.5*52cm
Standard Carton Gross Weight	11.93kg

CONTACT US

Address: No. 1, Baoqun Road, Shutian, Humen, Dongguan City, Guangdong Province
Phone: 400-699-1718